



ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

Non hygroscopic Fire-impregnated Western Red Cedar Frøslev Træ A/S



EPD HUB, HUB-1646

Published on 15 July 2024, last updated on 18 September 2024, valid until 15 July 2029.



GENERAL INFORMATION

MANUFACTURER

Manufacturer	Frøslev Træ A/S
Address	Jens P. L. Petersens Vej 1 DK-6330 Padborg
Contact details	info@froeslev.dk
Website	www.frøslev.dk

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804+A2:2019 and ISO 14025
PCR	EPD Hub Core PCR version 1.1, 5 Dec 2023
Sector	Construction product
Scope of the EPD	Cradle to gate with modules C1-C4, D
EPD author	Martin Oddershede, JJW Architects
EPD verification	Independent verification of this EPD and data, according to ISO 14025: ☐ Internal verification ☑ External verification
EPD verifier	Lucas Pedro Berman, as an authorized verifier acting for EPD Hub Limited

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT

Product name	Fire-impregnated Western Red Cedar
Place of production	Denmark Sweden (fire-impregnation)
Period for data	2023
Averaging in EPD	No averaging
Variation in GWP-fossil for A1-A3	0 %

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 cubic meter fire-impregnated cedar plank
Declared unit mass	425 kg
GWP-fossil, A1-A3 (kgCO2e)	2,70E+02
GWP-total, A1-A3 (kgCO2e)	-5,51E+02
Secondary material, inputs (%)	0
Secondary material, outputs (%)	101
Total energy use, A1-A3 (kWh)	2030
Net fresh water use, A1-A3 (m3)	0.68



PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

In Frøslev, we know wood. But not out of the blue. Since 1931, we have produced and delivered quality wood for everything from large constructions to private homes.

With Denmark's largest range of innovative, high-quality wood products and generations of knowledge, Frøslev offers the complete package – ensuring that any construction involving wood gets off to the right start and lasts for many years.

PRODUCT DESCRIPTION

Frøslev Cedar (Western Red Cedar) is a beautiful and exclusive wood species from Canada, naturally resistant to decay, fungi, and insect attacks. The wood has a lovely reddish-brown colour, is almost knot-free, and is one of the most beautiful materials you can use for facade and terrace cladding. Additionally, cedar is extremely durable, with a documented lifespan of at least 50 years on facades.

Further information can be found at www.frøslev.dk.

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass- %	Material origin
Metals	<1	-
Minerals	<1	-
Fossil materials	<1	-
Bio-based materials	100	Canada, EU

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	221.46
Biogenic carbon content in packaging, kg C	2.79

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 cubic meter fire- impregnated cedar plank
Mass per declared unit	425 kg
Reference service life	60

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).



PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Pro	oduct st	tage		embly age		Use stage End of life stage														
A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4		D			
x	x	x	MN D	MN D	MN D	MN D	MN D	MN D	MN D	MN D	MN D	x	x	x	x	x	x			
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./demol.	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling		

Modules not declared = MND. Modules not relevant = MNR.

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

The manufacturing process for the product involves several key steps, including the production of cedar planks, production of packaging materials, transportation, planing, fire impregnation, and final packaging. The fire impregnation of the product takes place in Sweden, conducted by Woodsafe Timber Protection.

TRANSPORT AND INSTALLATION (A4-A5)

Transportation impacts occurred from final products delivery to construction site (A4) cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions.

Please note that while this module has not been included within the system boundaries, the packaging (in module A3) and the waste produced (in modules C3-C4) have been considered.

PRODUCT USE AND MAINTENANCE (B1-B7)

This EPD does not cover the use phase.


Air, soil, and water impacts during the use phase have not been studied.

PRODUCT END OF LIFE (C1-C4, D)

At the end-of-life, in the demolition phase 100% of the waste is assumed to be collected as separate construction waste. The demolition process consumes energy in the form of diesel fuel used by building machines (C1). The dismantled wooden product is delivered to the nearest construction waste treatment plant where a default 50 km is used (C2). At the waste treatment plant, waste will be recycled (10 %) and recovered for energy (90%) (C3).



SYSTEM BOUNDARY





LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	Allocated by mass or volume
Ancillary materials	Allocated by mass or volume
Manufacturing energy and waste	Allocated by mass or volume

AVERAGES AND VARIABILITY

Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	0 %

This EPD is product and factory specific and does not contain average calculations.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. The EPD Generator uses Ecoinvent v3.8, Plastics Europe, Federal LCA Commons and One Click LCA databases as sources of environmental data.



ENVIRONMENTAL IMPACT DATA

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO₂e	-5,66E+02	2,05E-01	1,48E+01	-5,51E+02	MND	1,41E+00	1,88E+00	8,25E+02	3,92E+00	-3,08E+02								
GWP – fossil	kg CO₂e	2,45E+02	2,05E-01	2,49E+01	2,70E+02	MND	1,41E+00	1,88E+00	6,41E+00	3,32E-02	-3,07E+02								
GWP – biogenic	kg CO₂e	-8,12E+02	0,00E+00	-1,02E+01	-8,22E+02	MND	0,00E+00	0,00E+00	8,18E+02	3,89E+00	-4,03E-01								
GWP – LULUC	kg CO₂e	1,26E+00	7,57E-05	1,46E-01	1,41E+00	MND	1,40E-04	7,05E-04	2,76E-03	3,05E-05	-4,99E-01								
Ozone depletion pot.	kg CFC ₋₁₁ e	3,58E-05	4,72E-08	2,43E-06	3,83E-05	MND	3,01E-07	4,69E-07	4,28E-07	8,77E-09	-1,69E-05								
Acidification potential	mol H†e	2,09E+00	8,69E-04	1,78E-01	2,27E+00	MND	1,46E-02	5,99E-03	6,51E-02	2,48E-04	-2,38E+00								
EP-freshwater ²⁾	kg Pe	8,13E-02	1,68E-06	2,08E-03	8,34E-02	MND	4,66E-06	1,34E-05	1,18E-04	5,66E-07	-1,22E-02								
EP-marine	kg Ne	2,99E-01	2,58E-04	4,11E-02	3,40E-01	MND	6,47E-03	1,32E-03	3,02E-02	1,64E-04	-2,83E-01								
EP-terrestrial	mol Ne	3,83E+00	2,85E-03	5,07E-01	4,34E+00	MND	7,09E-02	1,47E-02	3,21E-01	9,23E-04	-3,32E+00								
POCP ("smog") ³⁾	kg NMVOCe	1,17E+00	9,12E-04	1,28E-01	1,30E+00	MND	1,95E-02	5,77E-03	7,92E-02	3,31E-04	-9,20E-01								
ADP-minerals & metals ⁴⁾	kg Sbe	3,87E-03	4,81E-07	1,42E-04	4,01E-03	MND	7,13E-07	4,60E-06	1,72E-05	9,95E-08	-2,75E-04								
ADP-fossil resources	MJ	4,76E+03	3,08E+00	4,93E+02	5,26E+03	MND	1,89E+01	3,00E+01	5,81E+01	6,73E-01	-3,89E+03								
Water use ⁵⁾	m³e depr.	3,01E+02	1,38E-02	1,43E+01	3,15E+02	MND	5,09E-02	1,39E-01	2,59E+01	4,03E-03	-4,70E+01								

¹⁾ GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.



ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	0,00E+00	2,37E-08	4,44E-07	4,67E-07	MND	3,92E-07	2,18E-07	6,81E-07	4,97E-09	-2,32E-05								
Ionizing radiation ⁶⁾	kBq U235e	0,00E+00	1,47E-02	1,00E+01	1,00E+01	MND	8,70E-02	1,55E-01	3,13E-01	3,25E-03	-7,65E+01								
Ecotoxicity (freshwater)	CTUe	0,00E+00	2,77E+00	2,40E+02	2,43E+02	MND	1,14E+01	2,50E+01	9,80E+01	6,84E-01	-7,26E+03								
Human toxicity, cancer	CTUh	0,00E+00	6,81E-11	1,81E-08	1,81E-08	MND	4,36E-10	6,49E-10	1,69E-08	2,19E-11	-9,87E-08								
Human tox. non-cancer	CTUh	0,00E+00	2,75E-09	2,39E-07	2,42E-07	MND	8,22E-09	2,54E-08	8,11E-07	6,91E-10	-2,99E-06								
SQP ⁷⁾	-	0,00E+00	3,55E+00	8,73E+02	8,76E+02	MND	2,46E+00	3,50E+01	1,75E+01	1,62E+00	-4,97E+03								

⁶⁾ EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Renew. PER as energy ⁸⁾	MJ	1,19E+03	3,47E-02	5,93E+02	1,78E+03	MND	1,08E-01	3,89E-01	2,56E+00	1,25E-02	-1,05E+03								
Renew. PER as material	MJ	8,51E+03	0,00E+00	8,96E+01	8,60E+03	MND	0,00E+00	0,00E+00	-8,57E+03	-3,40E+01	0,00E+00								
Total use of renew. PER	MJ	9,70E+03	3,47E-02	6,83E+02	1,04E+04	MND	1,08E-01	3,89E-01	-8,56E+03	-3,40E+01	-1,05E+03								
Non-re. PER as energy	MJ	5,03E+03	3,08E+00	4,82E+02	5,52E+03	MND	1,89E+01	3,00E+01	5,81E+01	6,73E-01	-3,89E+03								
Non-re. PER as material	MJ	0,00E+00	0,00E+00	1,05E+01	1,05E+01	MND	0,00E+00	0,00E+00	-7,14E+00	-3,40E+00	0,00E+00								
Total use of non-re. PER	MJ	5,03E+03	3,08E+00	4,93E+02	5,53E+03	MND	1,89E+01	3,00E+01	5,10E+01	-2,73E+00	-3,89E+03								
Secondary materials	kg	0,00E+00	8,56E-04	4,78E-01	4,79E-01	MND	7,41E-03	8,46E-03	1,24E-01	2,41E-04	-2,71E-01								
Renew. secondary fuels	MJ	0,00E+00	8,64E-06	3,03E+00	3,03E+00	MND	2,42E-05	7,46E-05	2,90E-04	9,23E-06	-3,89E-03								
Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00								
Use of net fresh water	m³	1,79E-01	3,99E-04	5,00E-01	6,79E-01	MND	1,15E-03	3,98E-03	-7,48E-02	7,20E-04	-3,07E+00								

⁸⁾ PER = Primary energy resources.





END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	С3	C4	D
Hazardous waste	kg	0,00E+00	4,09E-03	1,65E+00	1,65E+00	MND	2,53E-02	3,22E-02	3,18E-02	0,00E+00	-2,40E+01								
Non-hazardous waste	kg	0,00E+00	6,72E-02	9,12E+01	9,13E+01	MND	1,78E-01	5,60E-01	3,86E+02	2,73E+00	-9,66E+02								
Radioactive waste	kg	0,00E+00	2,06E-05	3,45E-03	3,47E-03	MND	1,33E-04	2,07E-04	5,51E-05	0,00E+00	-2,19E-02								

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	4,02E-03	4,02E-03	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00								
Materials for recycling	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	4,47E+01	0,00E+00	0,00E+00								
Materials for energy rec	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	3,85E+02	0,00E+00	0,00E+00								
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00								





ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO₂e	0,00E+00	2,03E-01	2,47E+01	2,49E+01	MND	1,39E+00	1,86E+00	6,13E+00	2,07E-01	-3,01E+02								
Ozone depletion Pot.	kg CFC ₋₁₁ e	0,00E+00	3,74E-08	2,12E-06	2,15E-06	MND	2,38E-07	3,71E-07	3,70E-07	6,96E-09	-1,38E-05								
Acidification	kg SO₂e	0,00E+00	6,75E-04	1,32E-01	1,33E-01	MND	1,04E-02	4,86E-03	4,60E-02	1,88E-04	-2,03E+00								
Eutrophication	kg PO ₄ ³e	0,00E+00	1,54E-04	8,53E-02	8,55E-02	MND	2,42E-03	1,03E-03	5,23E-02	7,94E-03	-4,39E-01								
POCP ("smog")	kg C ₂ H ₄ e	0,00E+00	2,64E-05	8,08E-03	8,11E-03	MND	2,28E-04	2,26E-04	1,53E-03	4,58E-05	-8,87E-02								
ADP-elements	kg Sbe	0,00E+00	4,66E-07	1,42E-04	1,42E-04	MND	7,02E-07	4,48E-06	1,53E-05	9,61E-08	-2,76E-04								
ADP-fossil	MJ	0,00E+00	3,08E+00	4,92E+02	4,95E+02	MND	1,89E+01	3,00E+01	5,81E+01	6,73E-01	-3,81E+03								



VERIFICATION STATEMENT

VERIFICATION PROCESS FOR THIS EPD

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? Read more online

THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

Lucas Pedro Berman, as an authorized verifier acting for EPD Hub Limited 15.07.2024



