

Declaration of Performance FT 02

Published 06.10.2013

Revised 14.01.2026

DoP FT 02 – Frøslev softwood

Prepared in accordance with the Construction Products Regulation (EU) No. 305/2011 and the Commission Delegated Regulation (EU) No. 574/2014.

Identification code of the product type

Cladding profile in pine (*Pinus sylvestris*), spruce (*Picea abies*), larch (*Larix sp.*) and Douglas fir (*Pseudotsuga menziesii*).

Intended use

Solid wood cladding for exterior use.

Manufacturer

Frøslev Træ A/S
Jens P.L. Petersens Vej 1
DK-6330 Padborg
Denmark

Authorised representative

Not relevant.

Systems for assessment and verification of constancy of performance

AVCP system 3 pursuant to Annex ZA.1, item 6.

Harmonised standard

EN14915:2013 Solid wood cladding - Characteristics, evaluation of conformity and marking.

Notified body's task

Not relevant.

Declared performance

Characteristic	Performance	Harmonised standard
Field of application	Solid wood cladding. Installation on wooden battens D-s2, d0 or better on substrates of reaction to fire class: • A2-s1, d0 min. 12 mm $\geq 525 \text{ kg/m}^3$ • A2-s1, d0 min. 9 mm $\geq 1300 \text{ kg/m}^3$ with $\lambda \geq 0.3 \text{ W/m}^\circ\text{K}$ • A1 min. 9.5 mm $\geq 830 \text{ kg/m}^3$ with $\lambda \geq 0.25 \text{ W/m}^\circ\text{K}$ Horizontal and vertical installation is allowed. Horizontal and vertical joints permitted.	DS/EN 14915:2013
Dimension*	Thickness $\geq 18 \text{ mm}$	
Density	Spruce: 470 kg/m^3 Pine: 530 kg/m^3 Larch: 600 kg/m^3 Douglas fir: 520 kg/m^3	
Reaction to fire	D-s2, d0 (determined by test)	
Water vapour resistance	NPD	
Thermal conductivity	NPD	
Sound absorption	NPD	
Biological durability	Spruce: Durability class 4 Pine: Durability class 3-4 Larch: Durability class 3-4 Douglas fir: Durability class 3-4	

*Surface profiling is permitted only if the total exposed surface area does not exceed 125 % of the original flat (plane) area.

Relevant technical documentation and/or specific technical documentation

This document, relevant data sheets, maintenance instructions, and other information can be viewed and downloaded at froeslev.dk/en/

The performance of the construction product identified above is in conformity with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer.

Padborg, 14.01.2026



Martin L. Petersen

CEO

Frøslev Træ A/S

Jens P. L. Petersens Vej 1, Frøslev
DK-6330 Padborg

T +45 74 67 06 00

info@froeslev.dk
froeslev.dk

CVR-nr. 14 24 83 31
Page 2/ 2