

Declaration of Performance FT 12

Published 30.05.2023

Revised 14.01.2026

DoP FT 12 – Frøslev ThermoAsh

Prepared in accordance with the Construction Products Regulation (EU) No. 305/2011 and the Commission Delegated Regulation (EU) No. 574/2014.

Identification code of the product type

Cladding profile in Frøslev ThermoAsh (thermally modified *Fraxinus excelsior*)

Intended use

Solid wood cladding for exterior use.

Manufacturer

Frøslev Træ A/S
Jens P.L. Petersens Vej 1
DK-6330 Padborg
Denmark

Authorised representative

Not relevant.

Systems for assessment and verification of constancy of performance

AVCP system 3 pursuant to Annex ZA.1, item 6.

Harmonised standard

EN14915:2013 Solid wood cladding - Characteristics, evaluation of conformity and marking.

Notified body's task

MeKa; Forest and Wood Products Research and Development Institute Ltd, Notified Body 2040.
ITT performed according to EN13501-1:2018 and with reference to K85/2021.

Declared performance

Characteristic	Performance	Harmonised standard
Field of application	Solid wood cladding. Installation on wooden battens D-s2, d0 or better on substrates of reaction to fire class: • A2-s1, d0 min. 12 mm $\geq 525 \text{ kg/m}^3$ • A2-s1, d0 min. 9 mm $\geq 1300 \text{ kg/m}^3$ with $\lambda \geq 0.3 \text{ W/m}^\circ\text{K}$ • A1 min. 9.5 mm $\geq 830 \text{ kg/m}^3$ with $\lambda \geq 0.25 \text{ W/m}^\circ\text{K}$ Horizontal and vertical installation is allowed. Horizontal and vertical joints permitted.	DS/EN 14915:2013
Dimension*	Thickness $\geq 19 \text{ mm}$	
Density	620 kg/m^3	
Reaction to fire	D-S1, d0 (determined by test)	
Water vapour resistance	NPD	
Thermal conductivity	NPD	
Sound absorption	NPD	
Biological durability	Durability class 1 (determined by test)	

*Surface profiling is permitted only if the total exposed surface area does not exceed 125 % of the original flat (plane) area.

Relevant technical documentation and/or specific technical documentation

This document, relevant data sheets, maintenance instructions, and other information can be viewed and downloaded at froeslev.dk/en/

The performance of the construction product identified above is in conformity with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer.

Padborg, 14.01.2026



Martin L. Petersen

CEO